




Technical data sheet

EGGER Decor Skirting boards

Application area

Preparation of wall finishes after installation of EGGER Laminate and Hybrid flooring.

Material data

Parameter	Unit			
Surface		Impregnated decor paper		
Carrier material		MDF (medium density fiberboard)		
Product		Décor Skirting board 6 cm cubical	Décor Skirting board 8 cm cubical	Beading profile 1,6 cm
Profile drawing				
Length	mm	2400	2400	2400
Thickness	mm	14	14	16
Width	mm	58	80	16
Color		See decor list skirting		
Paintable		No		
Method of use		<ul style="list-style-type: none"> - Egger Clipholder (distance 25-50 cm depending on the wall construction) - adhesive (SMP construction adhesive or 1K PU adhesive) - tacking (compressed-air tacker) 		<ul style="list-style-type: none"> - adhesive (SMP construction adhesive or 1K PU adhesive) - tacking (compressed-air tacker)
		Only mask skirtings with adhesive tapes that do not exceed an adhesive strength of 2N/cm in accordance with DIN EN 1939		

General data

Parameter		Test method
Formaldehyde Emission	E 1	EN 120
VOC-and Formaldehyde emission	A+	ISO 16000 part 3, 6, 9, 10
Light resistance	level 7	EN 20105
Cross section mass tolerance	± 8 %	RAL-RG 432
Longitudinal tolerance	+ 2 % / - 1%	RAL-RG 432
Recycling	recyclable	
Disposal	EWC: 17 02 01	
Cleaning	Using a vacuum cleaner With detergent pH < 8 and a damp cloth Avoid heavy accumulations of water	
Storage	Standing or lying on an even base Protect it from direct sunlight and moisture Climatic conditions: temperature 18° C, humidity 55 – 70 %	

Logistic parameters

Description	Parameter	Skirting 6 cm cubical	Skirting 8 cm cubical	Beading profile 1,6 cm with adhesive strip
Details package	Quantity	10	5	25
	Meter per package	24	12	60
	Dimension [mm]	2.410 x 135 x 65	2.410 x 86 x 69	2.410 x 125 x 45
	Weight [kg] +/- 10 %	9,7	9,1	6,7
Details pallet	Quantity	400	380	600
	Meter per pallet	960	912	1440
	Dimension [mm]	2.450 x 800 x 670	2.450 x 800 x 700	2.450 x 800 x 320
	Weight [kg] +/- 10 %	400	650	176

The tolerance for cross section mass, longitudinal dimensions as well as distortion and bend correspond RAL-RG 432.

Only use adhesive tapes that do not exceed an adhesive force (according to DIN EN 1939) of 2N/cm.

We confirm that in the manufacturing process, in the semi-finished goods and in the skirting's itself no top coating, no paints, no lacquers and no adhesives with organic solvents, biocides and free formaldehyde are used and contained.

Information

All above mentioned values were determined under laboratory conditions and defined laboratory materials and may deviate from these test values. For all the mentioned performance values inaccuracies are possible owing to the testing methods.

The information given above is based on our current state of knowledge and should be used for information of our product application. This should not be taken to as an assurance of certain quality of our products or their use for specific purposes. Subject to change, legal obligations cannot be derived from the information in this document. Existing commercial protective rights are to be observed.

A note on validity

This technical data sheet has been carefully drawn up to the best of our knowledge. It is intended for information only and does not constitute a guarantee in terms of product properties or suitability for specific applications. We accept no liability for any mistakes, errors in standards, or printing errors. In addition, technical changes may result from the further development of EGGER accessories as well as changes to standards and public law documents. This technical data sheet is not an instruction for use and is not a legally binding document.